


<p>CARPENTER LTD</p> <p>CARPET UNDERLAY</p>	<p><b>INDIVIDUAL SPECIFICATION SHEET</b></p> <p><b>GLOSSOP PLANT</b></p>	
<p>Amendment:</p>		<p>Date: 10/12/15</p>
<p><b>NEW IMPROVED DEEPSTEP</b></p>		
<p>CHARACTERISTIC</p> <p>ROLL LENGTH</p> <p>ROLL WIDTH</p> <p>DENSITY</p> <p>ROLL WEIGHT</p> <p>THICKNESS</p> <p>FLAMMABILITY (HOT METAL NUT TEST)</p> <p>THERMAL RESISTANCE</p> <p>IMPACT SOUND IMPROVEMENT INDEX</p> <p>CLASSIFICATION</p>	<p>SPECIFICATION</p> <p>11m min</p> <p>137cm ± 1%</p> <p>125Kg/m<sup>3</sup> ± 5%</p> <p>20.1Kg ± 5%</p> <p>11mm ± 5%</p> <p>LOW RADIUS of effect</p> <p>2.78 TOG</p> <p>46dB</p> <p>GD</p>	<p>TEST METHOD</p> <p>BS 4790:1987 (2003)</p> <p>BS 4745: 2005</p> <p>BS EN ISO 140- 8/ BS EN ISO 717-2</p> <p>BS EN 14499(2015)</p>
<p><b>Disclaimer</b></p> <p>Whilst ever effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Carpenter has no control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.</p> <p>Note: Intrastat No: 3918900090</p>		

