


CARPENTER LTD CARPET UNDERLAY	INDIVIDUAL SPECIFICATION SHEET GLOSSOP PLANT	
Amendment: 3		Date: 04/01/16
EXTRASTEP		
SUITABLE FOR USE WITH UNDERFLOOR HEATING		
CHARACTERISTIC	SPECIFICATION	TEST METHOD
ROLL LENGTH	11m min	
ROLL WIDTH	137cm ± 1%	
DENSITY	180Kg/m ³ ± 5%	
ROLL WEIGHT	17Kg ± 5%	
THICKNESS	6mm ± 5%	
INTERNATIONAL CODE FOR APPLICATION OF FIRE TEST PROCEDURES	Pass	IMO Resolution A653 (16) IMO Resolution MSC61(67) Annex 1 Part 5 and Annex 2 IMO Resolution MSC61(67) Annex 1 Part 2 and Annex 2
CLASSIFICATION OF REACTION TO FIRE PERFORMANCE IN ACCORDANCE WITH EN 13501-1:2007 +A1: 2009		Cfl s1
FLAMMABILITY (HOT METAL NUT TEST)	LOW RADIUS of effect	BS 4790:1987 (2003)
THERMAL RESISTANCE	1.5TOG	BS 4745: 1990/ISO 5085-1
IMPACT SOUND IMPROVEMENT INDEX	33dB	BS EN ISO 140- 8/ BS EN ISO 717-2
DOUBLE STICK CASTOR WHEEL CHAIR TEST	25000+	
CLASSIFICATION	HEAVY CONTRACT USE	BS 5808:1991(2005)

Disclaimer

Whilst ever effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Carpenter has no control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.

Note: Intrastat No: 3918900090

EG_203/02/310305