


CARPENTER LTD  CARPET UNDERLAY	<b>INDIVIDUAL SPECIFICATION SHEET</b>  <b>GLOSSOP PLANT</b>	
Amendment:		Date: 22/08/13
<b>ULTRASTEPE</b>		
<b>CHARACTERISTIC</b>  ROLL LENGTH  ROLL WIDTH  DENSITY  ROLL WEIGHT  THICKNESS  FLAMMABILITY (HOT METAL NUT TEST)  THERMAL RESISTANCE  IMPACT SOUND IMPROVEMENT INDEX  CLASSIFICATION	<b>SPECIFICATION</b>  11m min  137cm ± 1%  180Kg/m <sup>3</sup> ± 5%  26Kg ± 5%  9mm ± 5%  LOW RADIUS of effect  2.51 TOG  40dB  LUXURY USE	<b>TEST METHOD</b>       BS 4790:1987 (2003)  BS 4745: 2005  BS EN ISO 140- 8/ BS EN ISO 717-2  BS 5808:1991(2005)
<p><b><u>Disclaimer</u></b>          Whilst ever effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Carpenter has no control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.          Note: Intrastat No: 3918900090</p>		